

AFTER THREE DECADES, THE WORLD'S BEST SELLING ROTOR IS STILL NUMBER ONE.

FEATURES

- Model: 4"
- Arc setting: 40 to 360 degrees
- Nozzle choices: 27 total
- Nozzle racks: #1 to #12 red, 1.5 to 8.0 blue, #4 LA to #10 LA gray
- Factory installed rubber cover
- Through-the-top arc adjustment
- Quick check arc mechanism
- Water lubricated gear-drive
- Warranty period: 2 years

ADVANCED FEATURES

- Low angle nozzle choices

OPERATING SPECIFICATIONS

Radius: 22' to 52'

Flow rate: 0.5 to 14.1 GPM

Recommended pressure range: 25 to 70 PSI

Operating pressure range: 20 to 100 PSI

Precipitation rates: 0.4 in/hr approx.

Nozzle trajectory: Std = 25 degrees, Low angle = 13 degrees

FACTORY INSTALLED OPTIONS

Nozzles: #5 to #8 red, 1.5 to 4.0 blue

USER INSTALLED OPTIONS

Drain check valve (up to 4' of elevation; P/N 142300)



PGP-ADJ: Overall height: 7 $\frac{3}{8}$ "
Pop-up height: 4"
Exposed diameter: 1 $\frac{3}{4}$ "
Inlet size: $\frac{3}{4}$ " female NPT



SPECIFICATIONBUILDER

www.hunterindustries.com/PGP

MODELS	STANDARD FEATURES	NOZZLE OPTIONS
PGP-ADJ-B = 4" pop-up	Adjustable arc, with BLUE nozzle rack	1.5 to 4.0 = Factory installed nozzle number
PGP-ADJ = 4" pop-up	Adjustable arc, with RED nozzle rack	#5 to #8 = Factory installed nozzle number
PGP-ATR = Impact replacement	Adjustable arc, with RED nozzle rack	#7 = Factory installed nozzle number

EXAMPLES

PGP-ADJ	4" pop-up, adjustable arc
PGP-ADJ-B - 3.0	4" pop-up, adjustable arc, and 3.0 BLUE nozzle
PGP-ADJ - 07	4" pop-up, adjustable arc, and #7 RED nozzle